MIRAI

experience the future

DTL-642E500

42” / 107 cm LCD TV

full HD

HDMI DUAL HDMI

ChroMAX circuitry

SRS WOW

RHD 1920 x 1080

1200 : 1 Contrast

6,5ms Ultra Fast

MIRAI

experience the future

DTL-642E500

42” / 107 cm LCD TV

Screen Size	930.24(H) x 523.26 (V)
Aspect Ratio	16 : 9
Pixel Pitch	0.1615 (H) x 0.4845 (V)mm
Panel Resolution	1920 x 1080
Brightness	500 cd/m2
Contrast Ratio (typ.)	1200 : 1
Response Time (typ.)	6.5 ms
Viewing Angles (typ.)	176° (H) / 176° (V)
Display Color	16.7M
Tuner System	PAL, SECAM
Standard TV	B/G, D/K, I, L/L’
Control Panel	Power (On/OFF), Source Select (TV/SCART 1/SCART 2/VGA/ HDMI 1/HDMI 2), Menu (OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: CVBS/RGB(IN), TV(OUT) SCART 2: CVBS(IN), AV/TV(OUT) YPbPr via VGA, VGA Input, PC Audio In (for VGA), HDMI 1, HDMI 2, Headphone Output
Support Timing	480i / 480p / 576i / 576p / HDTV (720p / 1080i) / FULL HD (1080p)
Speaker	15W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Color Temp, White Balance, Picture Mode, Aspect Ratio, Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Channel Edit, Audio (Balance, Bass, Treble, SRS WOW 3D), Language
Picture Mode	User / Sport / Movie / Vivid / Game
PIP Function	1/2, 1/3 Window Size
Sleep Timer Function	Off / 15 min / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	1000 pages
Power Supply	AC 100-240 V, 2.9A, 50/60Hz
Power Consumption	< 280W
Safety / EMC	TUV-GS / Gost-R / CE / RoHS / WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord
VESA Mounting	400 x 200 mm
System Dimension	1053.5mm(W) x 798mm(H) x 319mm(D)
N.W.	29 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 - 567 10 56 FAX +31 (0)23 - 567 10 67
info@nl-mirai.com

www.mirai.eu